

# PRODUCT DATASHEET

## FL PFM 165 W 6500 K SYM 100 BK

**FLOODLIGHT 165 W | Versatile floodlight with 165 W power consumption**



### AREAS OF APPLICATION

- Replacement for floodlights with halogen lamps
- Outdoor use (IP65)
- Industry
- Public areas
- Construction areas
- Building facades

### PRODUCT BENEFITS

- Bright, robust and durable
- Safe and very uniform illumination, due to frosted and tempered glass diffuser
- No upper light output ratio (ULOR 0%) when mounted at 0° tilt
- Energy savings of up to 90 % compared to halogen lamp floodlights
- 5 years guarantee

### PRODUCT FEATURES

- Reflector-based, symmetric light distribution with 100° x 100° beam angle
- Integrated wide voltage driver, suitable for 100 - 277 V<sub>AC</sub>
- Surge protection: up to 6 kV (L/N-PE), 4 kV (L-N)
- Mounting bracket with 30° angle and wide rotation area
- Breather membrane to optimize air exchange, without compromising IP protection
- Pre-installed, flexible 1 m cable (H05RN-F), wrapped 3 x 1.0 mm<sup>2</sup> single wires



**TECHNICAL DATA**

Electrical data

Nominal wattage	165.00 W
Operating mode	Integrated LED driver
Nominal voltage	100...277 V
Power factor $\lambda$	> 0.90
Mains frequency	50/60 Hz
Max. no. of lum. on circuit break. B16 A	3
Max. no. of lum. on circuit break. C10 A	5
Max. no. of lum. on circuit break. C16 A	8
Inrush current	80.0 A
Total harmonic distortion	< 20 %
Inrush current time $T_{h50}$	1000 $\mu$ s

Luminaire control gear data

Low flicker	Yes
-------------	-----

Photometrical data


Color temperature	6500 K
Luminous flux	20000 lm
Luminous efficacy	121 lm/W
Standard deviation of color matching	$\leq 5$ sdc <sub>m</sub>
Light color (designation)	Cool Daylight
Color rendering index Ra	$\geq 80$

Light technical data

Beam angle	100 ° x 100 ° <sup>1)</sup>
------------	-----------------------------

<sup>1)</sup> ZMP\_110132

Dimensions & weight



<b>Length</b>	418.0 mm
<b>Width</b>	322.0 mm
<b>Height</b>	60.0 mm
<b>Product weight</b>	4800.00 g
<b>Cable length</b>	1000 mm

### Colors & materials

<b>Body material</b>	Aluminum
<b>Product color</b>	Black
<b>Housing color</b>	Black

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-30...+50 °C
----------------------------------	--------------

### Lifespan

<b>Number of switching cycles</b>	100000
<b>Lifespan L70/B50 at 25 °C</b>	70000 h
<b>Lifespan L80/B10 at 25 °C</b>	55000 h
<b>Lifespan L90/B10 at 25 °C</b>	35000 h

### Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Wall / Pole / Floor / Ceiling
<b>Low flicker</b>	Yes
<b>Product remark</b>	Available from September 2020

### Capabilities

<b>Adjustable</b>	Yes
<b>Dimmable</b>	No
<b>Type of connection</b>	Cable, 3-pole
<b>LED module replaceable</b>	Not replaceable

### Certificates & standards



<b>Protection class IK (shock resistance)</b>	IK08
<b>Glow Wire Test according to IEC 60695-2-12</b>	650 °C
<b>Photobiological safety group EN62778</b>	RG1
<b>Photobio. safety group acc. to EN62471</b>	RG1
<b>Protection class</b>	I
<b>Type of protection</b>	IP65
<b>Luminaire with limited surface temperature, class "D"</b>	No

<b>Standards</b>	CE/CB/ENEC/EAC/RoHS
------------------	---------------------

Logistical data

<b>Temperature range at storage</b>	-40...+70 °C
-------------------------------------	--------------

Light Distribution



LDC typ cone

LDC typ polar

SAFETY ADVICE


Max. wind load surface 0.102 m<sup>2</sup>

LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075423749	Shipping carton box 1	375 mm x 93 mm x 480 mm	5375.00 g	16.74 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



	A	B	C	LED	IP
65 W	750	150	8.5	2x M8	0.0484vF
80 W	650	150	10.5	2x M10	0.0614vF
125 W	1170	110	10.5	2x M10	0.0834vF
165 W	1170	110	12.5	2x M12	0.1024vF
200 W	1170	110	12.5	2x M12	0.1264vF



## REFERENCES / LINKS

For Guarantee see

▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.