

# PRODUCT DATASHEET

## FL PFM 200 W 6500 K SYM 100 BK

**FLOODLIGHT 200 W | Versatile floodlight with 200 W power consumption**



### AREAS OF APPLICATION

- Replacement for floodlights with halogen lamps
- Outdoor use (IP65)
- Industry
- Public areas
- Construction areas
- Building facades

### PRODUCT BENEFITS

- Bright, robust and durable
- Safe and very uniform illumination, due to frosted and tempered glass diffuser
- No upper light output ratio (ULOR 0%) when mounted at 0° tilt
- Energy savings of up to 90 % compared to halogen lamp floodlights
- 5 years guarantee

### PRODUCT FEATURES

- Reflector-based, symmetric light distribution with 100° x 100° beam angle
- Integrated wide voltage driver, suitable for 100 - 277 V<sub>AC</sub>
- Surge protection: up to 6 kV (L/N-PE), 4 kV (L-N)
- Mounting bracket with 30° angle and wide rotation area
- Breather membrane to optimize air exchange, without compromising IP protection
- Pre-installed, flexible 1 m cable (H05RN-F), wrapped 3 x 1.0 mm<sup>2</sup> single wires



## TECHNICAL DATA

### Electrical data

Nominal wattage	200.00 W
Operating mode	Integrated LED driver
Nominal voltage	100...277 V
Power factor $\lambda$	> 0.90
Mains frequency	50/60 Hz
Max. no. of lum. on circuit break. B16 A	3
Max. no. of lum. on circuit break. C10 A	5
Max. no. of lum. on circuit break. C16 A	8
Inrush current	80.0 A
Total harmonic distortion	< 20 %
Inrush current time $T_{h50}$	1000 $\mu$ s

### Luminaire control gear data

Low flicker	Yes
-------------	-----

### Photometrical data


Color temperature	6500 K
Luminous flux	25000 lm
Luminous efficacy	125 lm/W
Standard deviation of color matching	$\leq 5$ sdcn
Light color (designation)	Cool Daylight
Color rendering index Ra	$\geq 80$

### Light technical data

Beam angle	100 ° x 100 ° <sup>1)</sup>
------------	-----------------------------

<sup>1)</sup> ZMP\_110132

### Dimensions & weight



<b>Length</b>	454.0 mm
<b>Width</b>	354.0 mm
<b>Height</b>	62.0 mm
<b>Product weight</b>	6000.00 g
<b>Cable length</b>	1000 mm

## Colors &amp; materials

<b>Body material</b>	Aluminum
<b>Product color</b>	Black
<b>Housing color</b>	Black

## Temperatures &amp; operating conditions

<b>Ambient temperature range</b>	-30...+50 °C
----------------------------------	--------------

## Lifespan

<b>Number of switching cycles</b>	100000
<b>Lifespan L70/B50 at 25 °C</b>	70000 h
<b>Lifespan L80/B10 at 25 °C</b>	55000 h
<b>Lifespan L90/B10 at 25 °C</b>	35000 h

## Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Wall / Pole / Floor / Ceiling
<b>Low flicker</b>	Yes
<b>Product remark</b>	Available from September 2020

## Capabilities

<b>Adjustable</b>	Yes
<b>Dimmable</b>	No
<b>Type of connection</b>	Cable, 3-pole
<b>LED module replaceable</b>	Not replaceable

## Certificates &amp; standards

<b>Protection class IK (shock resistance)</b>	IK08
<b>Glow Wire Test according to IEC 60695-2-12</b>	650 °C
<b>Photobiological safety group EN62778</b>	RG1
<b>Photobio. safety group acc. to EN62471</b>	RG1
<b>Protection class</b>	I
<b>Type of protection</b>	IP65
<b>Luminaire with limited surface temperature, class "D"</b>	No

## Standards


CE/CB/ENEC/EAC/RoHS

## Logistical data

## Temperature range at storage

-40...+70 °C

## Light Distribution



LDC typ cone

LDC typ polar

## SAFETY ADVICE


Max. wind load surface 0.124 m<sup>2</sup>

## LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075423770	Shipping carton box 1	407 mm x 95 mm x 516 mm	6665.00 g	19.95 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## ADDITIONAL CATALOG INFORMATION



	A	B	C	LED	Power
95 W	150	158	8.5	2x M8	0.046 m²
80 W	150	158	10.5	2x M10	0.061 m²
125 W	170	178	10.5	2x M10	0.083 m²
165 W	170	178	12.5	2x M12	0.102 m²
200 W	170	178	12.5	2x M12	0.124 m²



REFERENCES / LINKS

For Guarantee see  
▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.