

LV HRC fuse base Sz. 00, 1-pole 160 A 690 V (1000 V) Flat terminal, 95 mm²



Model	
Product brand name	SETRON
Product designation	LV HRC fuse system
Design of the thread / of the nut	M8
Design of the thread / of the connection screw	M8
Design of the product	LV HRC fuse base
General technical data	
Number of poles	1
Size of fuse system / acc. to DIN EN 60269-1	Other
Usage category	Without
circuit-breaker / Design	3NH30
Supply voltage	
Current / at AC / rated value	160 A
Supply voltage	
• at AC / rated value	690 V
• at DC	440 V
Current	

Tripping residual / rated value / derated current / at 40 Cel	147.2 A
---	---------

Product details

Product component / Swivel mechanism	No
Maximum short-circuit current breaking capacity (Icu)	
<ul style="list-style-type: none"> • at AC / rated value 	120 kA
<ul style="list-style-type: none"> • at DC / rated value 	25 kA

Connections

<ul style="list-style-type: none"> • Connectable conductor cross-section / on saddle-type connector 	6 ... 70 mm ²
<ul style="list-style-type: none"> • Connectable conductor cross-section <ul style="list-style-type: none"> — on terminal strip 	1.5 ... 16 mm ²
<ul style="list-style-type: none"> — on plug-type connection 	2.5 ... 50 mm ²
Tightening torque / with screw-type terminals	14 N·m
Type of electrical connection	With flat-type terminal
<ul style="list-style-type: none"> • for main current circuit 	flat connector


Mechanical Design

Height	122 mm
Width	34 mm
Depth	60 mm
Mounting type	fixed mounting
Mounting type	
<ul style="list-style-type: none"> • bus-mounting 	No
Net weight	212 g

Certificates

Reference code	
<ul style="list-style-type: none"> • acc. to DIN EN 61346-2 	F
<ul style="list-style-type: none"> • acc. to DIN EN 81346-2 	F

General Product Approval			Declaration of Conformity	Test Certificates	
 CSA	 KEMA	 UR	 EG-Konf.	Special Test Certificate	Type Test Certificates/Test Report

Shipping Approval	other
 GL	Environmental Conformations

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NH3030>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NH3030>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NH3030

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>