

SENTRON, cylindrical fuse link, 22x58 mm, 80 A, gG, Un AC: 500 V



Model	
Product brand name	SENTRON
Product designation	Cylindrical fuse link
General technical data	
Operating class of the fuse link	gG
Size of the fuse link	22x58 mm
Type of voltage	AC
Current / at AC / rated value	80 A
Supply voltage / at DC	250 V
Operating voltage / rated value	500 V
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	7.5 W
Main circuit	
Operating current / Rated value	80 A
Product details	
Product component / striker	No
Mounting position	Any, preferably vertical

Net weight	55 g
------------	------

**Certificates**

Reference code	
<ul style="list-style-type: none"> <li>• acc. to DIN EN 61346-2</li> <li>• acc. to DIN EN 81346-2</li> </ul>	<p>F</p> <p>F</p>

<b>Declaration of Conformity</b>	<b>Test Certificates</b>
----------------------------------	--------------------------



[Miscellaneous](#)

**Further information**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NW6224-1>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3NW6224-1>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NW6224-1](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW6224-1)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

