

Auxiliary switch block, with screw terminal for contactor relays and motor contactors EN 50005 Ident. no. 22, 2 NO + 2 NC

General technical data	
Product brand name	SIRIUS
Suitability for use	Contactor relay and power contactor
Protection class IP on the front	IP20
Ambient temperature	
<ul style="list-style-type: none"> during storage 	-55 ... +80 °C
<ul style="list-style-type: none"> during operation 	-25 ... +55 °C
Mechanical service life (switching cycles) typical	10 000 000
Insulation voltage with degree of pollution 3 rated value	690 V
Surge voltage resistance rated value	6 kV
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	
<ul style="list-style-type: none"> instantaneous contact 	2
<ul style="list-style-type: none"> lagging switching 	0
Number of NO contacts for auxiliary contacts	
<ul style="list-style-type: none"> instantaneous contact 	2
<ul style="list-style-type: none"> leading contact 	0
Operating current of auxiliary contacts at AC-12	
<ul style="list-style-type: none"> at 24 V 	10 A
<ul style="list-style-type: none"> at 230 V 	10 A
<ul style="list-style-type: none"> maximum 	10 A
Operating current	
<ul style="list-style-type: none"> of auxiliary contacts <ul style="list-style-type: none"> at AC-14 <ul style="list-style-type: none"> at 125 V at AC-15 <ul style="list-style-type: none"> at 24 V at 230 V at 400 V at AC-15 at 690 V rated value 	10 A 10 A 5.6 A 3.6 A 2.3 A
Operating current	
<ul style="list-style-type: none"> of auxiliary contacts at DC-12 <ul style="list-style-type: none"> at 24 V at 110 V 	4 A 1.1 A

— at 220 V	0.5 A
Operating current	
• of auxiliary contacts at DC-13	
— at 24 V	10 A
— at 60 V	5 A
— at 110 V	1.14 A
— at 220 V	0.48 A

Installation/ mounting/ dimensions

Mounting type	snap-on mounting
Width	45 mm
Height	24 mm
Depth	25 mm







Connections/Terminals

Type of electrical connection for auxiliary and control current circuit	screw-type terminals
Type of connectable conductor cross-sections	
• for auxiliary contacts	
— finely stranded	
— with core end processing	2x (0.5 ... 1.0 mm ²), 2x (0.75 ... 2.5 mm ²)
• at AWG conductors for auxiliary contacts	2x (18 ... 12)

Safety related data

Product function positively driven operation acc. to IEC 60947-5-1	Yes
---	-----

Certificates/approvals

General Product Approval		Test Certificates
		
CCC	CSA	UL
		
		KC
		Special Test Certificate
Test Certificates	Shipping Approval	other
Type Test Certificates/Test Report		Confirmation
	PRS	
		
	RINA	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX4422-2A>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX4422-2A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX4422-2A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX4422-2A&lang=en

last modified:

07/25/2019